



Ref. Certif. No.

SE-95568

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE Power Supply

Name and address of the applicant

Globtek Inc
186 Veterans Drive
Northvale NJ 07647, USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

See page 2

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*961600P****, GT*961800P****

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

180401366SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 24 September 2019

intertek

Signature:

Gary Hu

Factories

GlobTek, Inc.
186 Veterans Dr. Nothvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 2.2A
Output: 12-54VDC, Max. 13.33A, Max. 180W
See model list for detail

Model	Input	Output voltage (Vdc)	Max. output current (A)	Max. output power (W)
GT*961600P**** GT*961800P****	100-240V~, 50-60Hz, 2.2A	12-14.9Vdc	13.33A	160W
GT*961600P**** GT*961800P****		15-18.9Vdc	11.33A	170W
GT*961600P**** GT*961800P****		19-54Vdc	9.47A	180W

Additional information (if necessary)

Explanation of model(s) GT*961600P****, GT*961800P****:

The 1st symbol “*” can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd symbol “*” can be “01” to “180”, denotes the rated output wattage designation from 1W to 180W, with interval of 1W.

The 3rd symbol “*” can be “12” to “54” or “12.0” to “54.0”, denote the standard rated output voltage designation from 12V to 54V, with interval of 0.1V.

The 4th symbol “*” =-T2 means desktop class II with C8 AC inlet
=-T2A means desktop class II with C18 AC inlet
=-T3 means desktop class I with C14 AC inlet
=-T3A means desktop class I with C6 AC inlet
=-TW means desktop with input wires without plug
=-TP means desktop with power cord and US plug

The last symbol “*” denote any six character = 0-9 or A-Z or () [] or – or blank for marketing purposes.

Group difference for CENELEC countries and national differences USA and Canada are considered.

Date: 24 September 2019

Signature: 